

CEN302AHD-AR (Dome Camera with Audio and Infrared)

Model: CEN302AHD-AR


High resolution, 1.3Mega Pixel, 12V DC



Features:

- Metal-cased IP66 weatherproof micro dome with fixed lens.
- Low power consumption.
 Easy installation on ceiling or wall, surface or flush mount.
 10 Infrared LEDs

Dimensions:





Specifications:

Image Sensor	1/3" CMOS AR0130
TV System	PAL/NTSC (optional)
Picture Elements	1280 (H) x 960 (V)
Sensitivity	0 Lux (IR LED On)
Scanning System	Progressive scan RGB CMOS
Synchronization	Internal
S/N Ratio	More than 44dB (AGC Off)
Auto Gain Control	(AGC) Auto
Electronic Shutter	Auto
BLC	Auto
Infrared Spectrum	850nm
Infrared LED	10 LEDs
Video Output	1 Vp-p, 75Ω,AHD
Audio	Available
Mirror	Optional
ICR	Available
Noise Redution	3D
Dymamic range	83.5 dB
Lens	f3.6mm Megapixel
Power Supply	9-18V DC
Power Consumption	120mA
Dimensions (ø X H)	77 x 60.3 mm
Net Weight	200 g
Weatherproof	IP66
Operating Temperature	-30° C ~ +70 ° C