

Anti Vandal Mini Dome Camera

CEN302-AHD SPECIFICATION



Overview

Our dome camera range, including a 25 degree angle adaptor, is designed for both exterior (non audio option only) and interior mounting on a vehicle, offers high-resolution imagery combined with anti-vibration capabilities and a compact form factor. The range also consists of an audio option (Model CEN302A), Infrared Option (Model CEN302R) and Audio / Infrared (CEN302AR).

Product Features

- ✓ Metal-cased IP67-IP69K weatherproof micro dome with fixed lens.
- ✓ Low power consumption.
- ✓ Easy installation on ceiling or wall, surface or flush mount.
- ✓ 10 Infrared LEDs (Optional - CEN302R and CEN302AR Models Only)
- ✓ Optional Built In Audio (CEN302A and CEN302AR Models)

Specifications

Models: CEN302-AHD, CEN302A-AHD, CEN302R-AHD, CEN302AR-AHD

| Specifications | |
|--------------------------|---|
| Image Sensor | 1/3" CMOS AR0130 |
| TV System | PAL |
| Picture Elements | 1280 (H) x 960 (V) |
| Sensitivity | 0 Lux (IR LED On) |
| Scanning System | Progressive scan RGB CMOS |
| Synchronization | Internal |
| S/N Ratio | More than 44dB (AGC Off) |
| Auto Gain Control | Auto |
| Electronic Shutter | Auto |
| BLC | Auto |
| Infrared Spectrum | 850nm |
| Infrared LED | 10 LEDs - CEN302R and CEN302AR Models |
| Video Output | 1 Vp-p, 75Ω,AHD |
| Audio | Available - CEN302A and CEN302AR Models |
| Mirror | Optional |
| ICR | Available |
| Noise Redution | 3D |
| Dymamic range | 83.5 dB |
| Lens | f3.6mm Megapixel |
| Power Supply | 9-18V DC |
| Power Consumption | 20mA |
| Dimensions (ø X H) | 77 x 60.3 mm |
| Net Weight | 200 g |
| Weatherproof/Water Proof | IP67 - IP69K |
| Operating Temperature | -30° C ~ +70 ° C |